

Eastto Kut PCX

INTRODUCTION : EASTTO KUT PCX forms a Milky Emulsion with water and contains rust corrosion Inhibitor and Biocide to prevent Bacterial growth in emulsion systems. This Oil has superior Cooling and Lubricating properties, which minimize Tool wear.

APPLICATION : Recommended for a variety of Cutting Operations on ferrous and nonferrous metals. It is used for Grinding, Milling Drilling, Turning, Boring, Punching, Reaming, Broaching and Tapping operations. It is also used in machine tool industries like Radial drilling machine, Conventional lathe, CNC rotating tool holder, CNC machining centre, Angle shearing and vertical machining centre .It is recommended to use 3 – 5% concentrations for all types of operations.

PERFORMANCE LEVEL : Meets IS-1115 – 1986 (Reaffirmed 2002) specifications.

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO KUT PCX
Kinematic Viscosity at 40°C., cSt, Min.	35
Emulsion test in 400 ppm Hard Water	Passes
Casr Iron Corrosion Test (20:1 Emulsion)	Passes
Emulsion test, 5: 1 and 20 : 1	Passes
Frothing test. 5 : 1 and 20 : 1 ratio in 200 ppm hardness (as Ca CO ²)	Passes
Copper strip corrosion test at 100°C for 3 hours)	1a
Thermal Stability Test	Shall pass the test

PACKING: 210 Litres Drums



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Kut PCX