## **Eastto** Semi - Synth Cutting Oil

**INTRODUCTION: EASTTO SEMI - SYNTH CUTTING OIL** is premium quality semi synthetic cutting oil for machining and grinding of ferrous and non - ferrous metal and alloys. It forms a translucent emulsion to provide a clear view of work piece and tools with extended tool life and improved finish of work piece,. It resists bacterial attack to control the emulsion stability with excellent rust and corrosion protections. This semi synthetic coolant is ideal for individual and central sump system with low foaming tendency and dissipates heat faster.

**APPLICATION:EASTTO SEMI – SYNTH CUTTING OIL** is excellent for the machining of all ferrous and non – ferrous metals and the applications include grinding, milling drilling, turning, boring, punching, reaming, sawing, broaching and tapping etc.

**PERFORMANCE LEVEL:** EASTTO SEMI – SYNTH CUTTING OIL is a proprietary product.

## TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO SEMI – SYNTH CUTTING OIL
CONCENTRATE	
Appearance and Colour	Yellow Coloured Liquid
Kinematic Viscosity at 40°C, cSt	40
5% EMULSION	
Appearance	Translucent Emulsion with 400 ppm water
pH of 5% emulsion in distilled water	9.2
Kinematic Viscosity at 40°C, cSt	Passes
Kinematic Viscosity at 40°C, cSt	Passes

**PACKING:** 210 Litres Drums









## **Eastern Petroleum Private Limited**

Road Off

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990 Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





## **Eastern Petroleum Private Limited**

an ISO 9001-2008 certified company



**Eastto** Semi Synth Cutting Oil