

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Fax: +91 - 22 - 4232 4131, 2524 1895 Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:	EASTTO PET 60 - SODIUM PETROLEUM SULPHONATE
INTRODUCTION:	EASTTO PET 60 is a sodium petroleum sulphonate. It is specially designed for use in Emulsifier for soluble cutting oils as well as Metal working oils.
APPLICATION:	It is widely used in the manufacture of Soluble Cutting Oils, Emulsifiers for Soluble Cutting Oils, Rust Preventives, Leather Chemicals, Fat Liquor, Metal Treatment Chemicals, Metal working fluid, Wire drawing oils, Corrosion inhibitors, Protective coatings, Degreasing agent, Fuel additive, Lube oil additive, Textile Auxiliaries, Ore Flotation Chemicals and Inks. This product is miscible with Oil and Solvent.







Emulsifiers for Soluble Cutting Oils.

PERFORMANCE LEVEL: Proprietary product

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTOPET 60
Appearance	Dark Brown Viscous Liquid
Active Matter (as Sodium Sulphonate, Wt. %)	60
Mineral Oil Content, Wt. %	32
Inorganic Salt (as Sodium Sulphate, Wt. %)	1.0
Water, Wt. %	3.0
Alkalinity (as NaOH, Wt. %)	0.15 Max.
Acidity, Wt. %	Nil.
Average Molecular Weight	465

PACKING: 200 kgs of MS Barrel

Date of Issue : 20.12.2014

Date of Revision: 10.08.2016

PDS No. 20.01.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

