

Eastto 2T OIL

Eastto Two Stroke Engine Oil

INTRODUCTION: EASTTO 2T OIL is low smoke semi-synthetic two stroke engine oil developed to meet the critical requirements of two stroke engines manufactured by all leading auto makers. It is blended from selected base stocks and special additives to minimise spark plug fouling and pre - ignition, prevent rusting, minimise deposit formation and provide protection against seizure, scuffing and wear. It is specifically formulated to give additional advantage of lower consumption of fuel. It contains a diluent for easy mixing with gasoline and is dyed green for easy identification.

APPLICATION: EASTTO 2T OIL is recommended for lubrication of mopeds, scooters, motorcycles and autorickshaws, operating on two stroke engines. The recommended dosage is 20 ml of oil per litre of petrol.

PERFORMANCE LEVEL: EASTTO 2T OIL meets the performance level of JASO FC specifications.

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO 2T OIL
Kinematic Viscosity at 40°C., cSt,	50.0 to 60.0
Flash Point, COC, °C. Min.	200
Sulphated Ash, % by Weight, Max	0.25
Pour Point, °C. Max.	(-)12

PACKING: 210 Litres Drum, 50 Litres, 20 Litres, 5 Litres, 1 Litre



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
2T Oil