



Eastern Petroleum Private Limited

Regd. Off:
213, Swastik Chambers, C.S.T. Road,
Chembur, Mumbai - 400 071. Maharashtra, India
Tel. : +91-22-4232 4121 / 2529 9990
Fax : +91-22-4234 4131 / 2524 1695
Email : office@easternpetroleum.in
Web : www.easternpetroleum.in

PRODUCT DATA SHEET

PRODUCT: EASTTO SHOCK ABSORBER OIL 12, 18

GRADE: 12 & 18

INTRODUCTION: EASTTO SHOCK ABSORBER OIL 12, 18 are blended from high viscosity index oils and specially selected additives to provide excellent anti-wear, anti-rust and anti-oxidation properties. EASTTO SHOCK ABSORBER OIL 12, 18 have very good chemical stability, excellent seal compatibility and very low pour point (for usage over wide range of temperature variations) with excellent dampening characteristics.

APPLICATION: EASTTO SHOCK ABSORBER OIL 12, 18 are recommended for use in shock absorbers

PERFORMANCE LEVEL: Proprietary

TYPICAL PROPERTIES

| CHARACTERISTICS | EASTTO SHOCK ABSORBER OIL 12 | EASTTO SHOCK ABSORBER OIL 18 |
|------------------------------------|------------------------------|------------------------------|
| Kinematic Viscosity at 40°C., cSt, | 11.0 – 13.0 | 17.0 – 19.0 |
| Viscosity Index, Min. | 45 | 45 |
| Flash Point, COC, °C, Min. | 145 | 160 |
| Pour Point, °C, Max. | (-) 39 | (-) 36 |

PACKING: 210 Litres Drums.

Date of issue: 01.07.2009

PDS No. 01.45.01 – 01.46.02

