

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071, MH, India.

(SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. Product name and Company identification

Product Name	:	EASTTO BRAKE FLUID DOT 3
Product Use	:	Automotive brake fluid
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jawahar industrial Estate, Kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No.	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

2. Composition / Information of Ingredients

	Ingredient name	CAS Number	% by wt
	Triethylene glycol monobutyl ether Di ethylene glycol Tetra ethylene glycol mono ethyl ether Di ethylene glycol monobutyl ether	143-22-6 111-46-6 112-50-5 112-34-5	45 - 35 10 - 20 8 - 20 5 - 15
3.	Hazards identification	Non dangerous substance	
	Physical state	Liquid	
	Human Health Effects		
	Eyes	Not expected to cause Eyes irritation	
	Skin	Not expected to cause skin irritation	
	Inhalation	Not expected to cause any side effect while inhalation	

4. First Aid Measures

Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Skin contact	Immediately wash affected area with soap and water. Remove contaminated clothing and shoes. Get medical attentions if a symptom occurs.
Eye contacts	In case of contact immediately wash eyes with plenty of water.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately. Get medical attention if symptoms occur.

5. Fire-fighting Measures

Flammability of product	Combustible liquid
Extinguishing Media Suitable Not suitable	Use dry chemical, carbon dioxide (CO_2) , or foam Do not use water.

6. Accidental Release Measures

Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.	
Environmental precautions	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform local authorities if this cannot be	



Eastern Petroleum Pvt. Ltd. an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

prevented. Pick up free liquid for recycling or disposal. The residual fluid can be transferred to another container. Clean up method- small spillage Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulation. Clean up methods - large spillage Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for

7. Handling and Storage

Handling

Storage

Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment, vapours or mists might be released and require a well ventilated workplace. Store at ambient temperature or with lowest necessary heating as required for ease of handling.

8. **Exposure Controls / Personal Protection**

Control parameters Exposure via air and normal handling Personal protection equipment **Respiratory protection** Avoid inhalation use suitable mask with filter if necessary. Hand protection Wear fluid-resistant protective gloves if there is a risk of skin contact. Eye protection For eyes protection wear safety goggles. Use protective cloths and gloves. Skin and body protection Act in accordance with good industrial Hygiene and safety practice. Hygienic measures

small spills.

9 **Physical and Chemical Properties**

CHARCTERISTICS	EASTTO BRAKE FLUID DOT 3
Physical state	Liquid
Odour	Mild
Kinematic viscosity @ 40 °C, cst	55
Colour	Green
Solubility in water	Insoluble
рН	N.A
Flash point ⁰ C	200

10. **Stability and Reactivity**

	Reactivity and stability Conditions to avoid Hazardous decomposition products Hazardous polymerization	Stable at normal conditions and decompose at higher temperature. Excessive heating and highly oxidizing agents Hazardous decomposition products are not expected to form during normal storage. Polymerization will not occur.
11.	Toxicological Information	
	Potential chronic health effects Carcinogenicity	No known significant effects or critical hazards.
12.	Ecological Information	
	Environment effect:	Will not have chronic effect on aquatic environment
13.	Disposal considerations	
	Waste disposal procedure:	Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

14.	Transport Information	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)
15.	Regulatory Information	Not classified as hazardous.
16.	Other Information	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.