

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

## **MATERIAL SAFETY DATA SHEET**

1. Product name and Company identification

Product Name : EASTTO BRAKE FLUID DOT 4

Product Use : Automotive brake fluid

Supplier : Eastern Petroleum Pvt. Ltd

235-239, Jawahar industrial Estate, Kamothe, Panvel,

Dist-Raigad, Maharashtra: 410209

**Telephone No.** : 91-22-2743 1694, 91-22-2743 3819.

Email : sales@easternpetroleum.in

## 2. Composition / Information of Ingredients

Ingredient name	CAS Number	% by wt
Triethylene glycol monobutyl ether	143-22-6	20 - 35
Di ethylene glycol	111-46-6	10 - 20
Tetra ethylene glycol mono ethyl ether	112-50-5	35 – 45
Di ethylene glycol monobutyl ether	112-34-5	5 - 15

3. Hazards identification Non dangerous substance

Physical state Liquid

**Human Health Effects** 

Eyes Not expected to cause Eyes irritation

**Skin** Not expected to cause skin irritation

Inhalation Not expected to cause any side effect while inhalation

4. First Aid Measures

**Inhalation** If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Skin contact Immediately wash affected area with soap and water. Remove contaminated

clothing and shoes. Get medical attentions if a symptom occurs.

Eye contacts In case of contact immediately wash eyes with plenty of water.

**Ingestion**Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous

quantities of this material have been swallowed, call a physician immediately.

Get medical attention if symptoms occur.

5. Fire-fighting Measures

Flammability of product Combustible liquid

**Extinguishing Media** 

Suitable Use dry chemical, carbon dioxide (CO<sub>2</sub>), or foam

Not suitable Do not use water.

6. Accidental Release Measures

Personal precautions Wear suitable protection clothing and equipment. Remove contaminated clothes

as soon as possible.

Environmental precautions

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform local authorities if this cannot be

an or other appropriate barriers. Inform total authorities in this same of

**EASTTO BRAKE FLUID DOT 4** 

Revision No. 3

Date of issue: 04.09.2014 Date of revision: 26.08.2016



an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

prevented. Pick up free liquid for recycling or disposal. The residual fluid can be

transferred to another container.

Clean up method- small spillage Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly

marked container for disposal in accordance with local regulation.

Clean up methods - large spillage Prevent from spreading by making a barrier with sand, earth or other

containment material. Reclaim liquid directly or in an absorbent. Dispose of as for

small spills.

7. Handling and Storage

Storage

Handle in accordance with good industrial hygiene and safety practices. If

handled at elevated temperatures or with high speed mechanical equipment, vapours or mists might be released and require a well ventilated workplace. Store at ambient temperature or with lowest necessary heating as required for

ease of handling.

8. Exposure Controls / Personal Protection

Control parameters Exposure via air and normal handling

Personal protection equipment

**Respiratory protection** Avoid inhalation use suitable mask with filter if necessary.

**Hand protection** Wear fluid-resistant protective gloves if there is a risk of skin contact.

**Eye protection**For eyes protection wear safety goggles. **Skin and body protection**Use protective cloths and gloves.

**Hygienic measures**Act in accordance with good industrial Hygiene and safety practice.

## 9. Physical and Chemical Properties

CHARCTERISTICS	EASTTO BRAKE FLUID DOT 4
Physical state	Liquid
Odour	Mild
Kinematic viscosity @ 40 °C, cst	55
Colour	Green
Solubility in water	Insoluble
pH	N.A
Flash point <sup>0</sup> C	200

## 10. Stability and Reactivity

Reactivity and stability Stable at normal conditions and decompose at higher temperature.

Conditions to avoid Excessive heating and highly oxidizing agents

Hazardous decomposition products Hazardous decomposition products are not expected to form during normal

storage.

Hazardous polymerization Polymerization will not occur.

## 11. Toxicological Information

Potential chronic health effects

**Carcinogenicity** No known significant effects or critical hazards.

# 12. Ecological Information

### **Environment effect:**

Will not have chronic effect on aquatic environment

## 13. Disposal considerations

# Waste disposal procedure:

Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.

**EASTTO BRAKE FLUID DOT 4** 

Revision No. 3

Date of issue: 04.09.2014 Date of revision: 26.08.2016



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

Date of issue: 04.09.2014

Date of revision: 26.08.2016

14.	Transport Information	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)
15.	Regulatory Information	Not classified as hazardous.
16.	Other Information	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.