

CIN NO:U24100MH1964PTC012931

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in

PRODUCT DATA SHEET

PRODUCT: EASTTO GEAR OIL EXTRA EP 80W-90 GL-5, 85W-140 GL-5

INTRODUCTION:

EASTTO GEAR OIL EXTRA EP 80W-90, 85W-140 are high performance, multipurpose, thermally stable and heavy duty automotive gear lubricants. They are blended from highly refined base stocks with high performance EP additive system for providing excellent load carrying capacity to protect gear equipment against surface distress (i.e. spalling, pitting, scoring and wear) under heavily loaded conditions. Special inhibitor system has also been incorporated to provide excellent oxidation stability to resist oil degradation and thickening during long periods of severe high temperature operations. High viscosity index and low pour point assure good film strength for gear protection at both high and low temperatures.

APPLICATION:

EASTTO GEAR OIL EXTRA EP 80W-90, 85W-140 are recommended for automotive differentials operating under low speed, high speed and high torque conditions, heavy duty non-synchronized manual transmission and trans axles where ambient temperature vary widely.





Heavy duty automotive gear.

PERFORMANCE LEVEL:

Meets the performance level of API service classification GL-5, IS: 1118-1992 EP Type GL-5, US Military MIL-L-2105D

TYPICAL PROPERTIES	EASTTO GEAR OIL EXTRA EP 80W-90	EASTTO GEAR OIL EXTRA EP 85W-140
Kinematic Viscosity at 100°C, cst	14	26
Viscosity Index, Min.	95	95
Flash Point, COC, °C.	180	200
Pour Point, °C.	- 24	- 15

PACKING: 210 Liters Drums Date of issue: 06.09.2014 Date of revision: 26.08.2016 PDS No. 01.31.02/01.31.04

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

