

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990
Email: office@easternpetroleum.in, Web:www.easternpetroleum.in

CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:	EASTTO GEAR OIL EP 90, 140	
INTRODUCTION:	EASTTO GEAR OIL EP 90, 140 are extreme pressure automotive gear lubricants. These oils are blended from specially selected base stocks and additives to provide extreme pressure, anti-rust, anti-corrosion characteristics.	
APPLICATION:	EASTTO GEAR OIL EP 90, 140 oils are recommended for passenger car, bus and highway truck for the lubrication of hypoid, spiral bevel and worm gear axles and also manual transmission for which an extreme pressure gear lubricant of this type is required.	







Hypoid gear Spiral Bevel Worm gear

PERFORMANCE LEVEL:

EASTTO GEAR OIL EP 90, EP 140 meets the performance level of API service classification GL-4, IS: 1118-1992 EP Type GL-4.

TYPICAL PROPERTIES	EASTTO GEAR OIL EP 90	EASTTO GEAR OIL EP 140
Kinematic Viscosity at 100°C, cst	17	30
Viscosity Index	90	90
Flash Point, COC, °C.	190	200
Pour Point, °C.	- 9	- 9

PACKING: 210 Liters Drum

Date of issue: 09.09.2014

Date of revision: 26.08.2016

PDS No. 01.30.01 - 01.30.02

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

