

## Product Data Sheet

**PRODUCT:****EASTTO GEN SET OIL SAE 40****INTRODUCTION:**

**EASTTO GEN SET OILSAE 40** is blended from highly refined base stocks with high viscosity index and additives that impart detergent, dispersant, anti-oxidant and anti-wear properties. Besides lowering the maintenance cost, **EASTTO GEN SET OIL SAE 40** enhances the engine life with less wear and tear and controlling sludge and varnish.

**APPLICATION:**

**EASTTO GEN SET OIL 40** is recommended for used as crankcase oils for slow, medium and high speed stationary diesel engines, e.g. Generator Set Oil etc.

**PERFORMANCE LEVEL:**

**EASTTO GEN SET OIL SAE 40** meets the performance level of API CD, IS: 13656-2014, EDL-2

**TYPICAL PROPERTIES**

CHARACTERISTICS	EASTTO GEN SET OIL SAE 40
Kinematic Viscosity at 100°C, cst	14.5
Flash Point, COC, °C, Min.	220
TBN, mg KOH / gm	10
Pour Point, °C	-6

**PACKING:** 210 Litres Drum

Date of issue: 06.09.2014

Date of revision: 26.08.2016

PDS No. 01.15.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

