

PRODUCT DATA SHEET

PRODUCT: EASTTO MOTOR OIL SAE 30, 40, 50

INTRODUCTION: EASTTO MOTOR OIL SAE 30, 40, 50 are blended from highly refined base stocks with high viscosity index and additives that impart detergent, dispersant, anti-oxidant and anti-wear properties.

APPLICATION: EASTTO MOTOR OIL SAE 30, 40, 50 are recommended for use as crankcase oils for older type four stroke gasoline engines, stationary diesel engines, particularly for commercial fleet operation.



Generator



Four Stroke Vehicle

PERFORMANCE LEVEL: EASTTO MOTOR OIL SAE 30, 40, 50 meet the performance level of API CC/SC, IS: 13656-2014, EPL-1/EDL-1, SAE 30, 40, 50

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO MOTOR OIL SAE 30	EASTTO MOTOR OIL SAE 40	EASTTO MOTOR OIL SAE 50
Kinematic Viscosity at 100°C, cst	11	14	19
Flash Point °C, Min.	220	220	220
TBN, mg KOH / gm	5.0	5.0	5.0
Pour Point, °C	- 6	- 6	- 6

PACKING: 210 Litres Drum

Date of issue: 06.09.2014

Date of revision: 26.08.2016

PDS No. 01.01.01 – 01.01.03

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

