

PRODUCT DATA SHEET

PRODUCT: EASTTO SHOCK ABSORBER OIL 12, 18

INTRODUCTION: EASTTO SHOCK ABSORBER OIL 12, 18 are blended from high viscosity index oils and specially selected additives to provide excellent anti-wear, anti-rust and anti-oxidation properties. EASTTO SHOCK ABSORBER OIL 12, 18 have very good chemical stability, excellent seal compatibility and very low pour point (for usage over wide range of temperature variations) with excellent dampening characteristics.

APPLICATION: EASTTO SHOCK ABSORBER OIL 12, 18 are recommended for use in shock absorbers.



TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO SHOCK ABSORBER OIL 12	EASTTO SHOCK ABSORBER OIL 18
Kinematic Viscosity at 40°C., cSt,	11.0 – 13.0	11.0 – 13.0
Viscosity Index, Min.	45	45
Flash Point, COC, °C, Min.	145	160
Pour Point, °C, Max.	(-) 39	(-) 36

PACKING: 210 Litres Drums

Date of issue: 01.07.2009

Date of revision: 01.07.2009

PDS No. 05.30.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

