

Eastto HYDRAULIC OILS HLP ZF

GRADE: VG 32, 46, 68, AND 100

INTRODUCTION:

Eastto HYDRAULIC OILS HLP ZF comprise a range of high performance hydraulic oils blended from solvent refined high viscosity index paraffinic mineral oils and zinc free ashless additives. Good thermal and oxidative stability provide reliable and extended oil life in severe applications with minimal deposit formation that gives cleaner system and reduced frequency of filter changes. Also these oils also have excellent water separation characteristics, hydrolytic stability and compatibly to seals normally used in hydraulic systems.

APPLICATION:

EASTTO HYDRAULIC OILS HLP ZF are recommended for hydraulic systems requiring excellent anti-wear and superior oxidation performance with ultra fine filtration and compatibly with elastomer materials.

PERFORMANCE LEVEL: IS: 10522:1983 [Reaffirmed 1998]

IS: 11656:1986 [Reaffirmed 2002]

DIN 51524 Part II

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO HYDRAULIC OILS HLP ZF			
	32	46	68	100
KV at 40°C, cSt	30 - 34	44 - 48	66 - 70	95 - 105
Viscosity Index, Min.	95	95	95	95
Flash Point, COC, °C, Min.	210	220	220	220
Pour Point, °C. Max.	-6	-6	-6	-6

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto

Hydraulic Oils HLP ZF

Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990

Email: office@easternpetroleum.in, office@eastto.in,

Web: www.easternpetroleum.in, www.eastto.in

