

Eastto Steel Oils

GRADE: VG 257, 320, 460 & 680

INTRODUCTION :

EASTTO STEEL OIL 257, 320, 460 & 680 are premium quality heavy duty bearing oils with high viscosity index, superior oxidation and good thermal stability. They have unique demulsibility, antifoaming, antioxidation, antirust characteristics and excellent film strength property to minimise wear in roll-neck bearing of steel mills.

APPLICATION : EASTTO STEEL OIL 257, 320, 460 & 680 are recommended for the Morgan bearings of steel mills, e.g. is in the Plate Mills, Wire Rod Mills, Merchant Mills, Blooming and Billet Mills, Rail and Structural Mills etc. with various viscometric grades to take care of heavier load in the presence of water.

PERFORMANCE LEVEL :

TYPICAL PROPERTIES:

EASTTO STEEL OILS				
CHARACTERISTICS	257	320	460	680
Kinematic Viscosity @ 40°C, cSt.	255 to 265	310 to 330	440 to 480	660 to 700
Viscosity Index	90	90	90	90
Flash Point, °C (COC), Min.	210	220	220	240
Pour Point, °C, Max.	-6	-6	-6	-6

PACKING : 210 Litres Drum



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Steel Oils



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

