

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. Product name and Company identification

Product Name	:	EASTTO MULTIPURPOSE GREASE NLGI 1
Product use	:	Industrial and Automotive use
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jawahar industrial estate, kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No.	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

2. Composition / Information of Ingredients

Ingredient name	CAS No.	% by wt	
Mineral base oil	64742-54-7	86 – 93	
Thickener: Lithium mixture Additive components:	1310-66-3	5 – 10	
Antioxidant, Antirust, Anti-wear	Mixture	2 - 4	
Hazards identification			
Physical state	Semi solid		
Human Health Effects			
Eves	Not irritating		
	Mineral base oil Thickener: Lithium mixture Additive components: Antioxidant, Antirust, Anti-wear Hazards identification Physical state Human Health Effects	Mineral base oil64742-54-7Thickener: Lithium mixture1310-66-3Additive components:1310-66-3Antioxidant, Antirust, Anti-wearMixtureHazards identificationMixturePhysical stateSemi solid	Mineral base oil 64742-54-7 86 – 93 Thickener: Lithium mixture 1310-66-3 5 – 10 Additive components: Antioxidant, Antirust, Anti-wear Mixture 2 - 4 Hazards identification Physical state Semi solid Human Health Effects Image: Semi solid Image: Semi solid

Risk is not possible under normal conditions of use.	

Not Irritating

Non hazardous

4. First Aid Measures

Chemical Hazard

Skin

Inhalation

Inhalation	Remove the person to fresh air. Get medical attention.
Skin contact	Wash the affected area repeatedly with soap and water.
Eye contacts	In case of contact immediately wash eyes with plenty of water.
Ingestion	Small quantity can cause stomach discomforts, nausea and vomiting.

5. Fire-fighting Measures

Flammability of product	Combustion is likely to give rise to a complex mixture of gases and airborne particulates, including carbon monoxide, oxides of sulphur, lead compounds and unidentified organic and inorganic compounds.
Extinguishing Media Suitable Not suitable	Use dry chemical, carbon dioxide (CO ₂), or foam Do not use water.

6. Accidental Release Measures

Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.
Environmental precautions	Prevent spills to enter and spread to drains, sewers, watercourses and soil. Contact local safety authorities.
Methods for cleaning up	Contain leaking product with sand, earth or other suitable inert materials.



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

7. H	landling	and	Storage
------	----------	-----	---------

	Handling	Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment,
	Storage	vapors or mists might be released and require a well ventilated workplace. Store at ambient temperature or with lowest necessary heating as required for ease of handling.
8.	Exposure Controls / Personal Protection	

Control parameters	Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.
Personal protection equipment	
Respiratory protection Hand protection Eye protection Skin and body protection Hygienic measures	Avoid inhalation use suitable mask with filter if necessary. Wear grease-resistant protective gloves if there is a risk of skin contact. For eyes protection wear safety goggles. Use protective cloths and gloves. Act in accordance with good industrial Hygiene and safety practice.

9. **Physical and Chemical Properties**

Characteristics	NLGI 1
Physical state	Semi Solid
Colour	Dark brown
Odour	Mild
Worked Penetration @ 25°C	310 - 340
рН	N.A
Solubility in water	Insoluble
Vapour pressure(mmHg@25)	Low
Drop Point °C	192
Auto- ignition Temperature °C	>320

10 **Stability and Reactivity**

e of in Contact isposal.
CAO)
ł



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

16. Other Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.