

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web: www.easternpetroleum.in CIN NO: U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. Product name and Company identification

Product Name	:	EASTTO NEAT CUTTING OIL 522
Product Use	:	Industrial Neat cutting oil
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jawahar Industrial Estate, Kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No.	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

2. Composition / Information of Ingredients

	Ingredient name	CAS Number	% by wt
	Mineral base oil Proprietary additives	64742-65-0 Mixture	88 - 94 6 -12
3.	Hazards identification	Non dangerous substance	
	Physical state	Liquid	
	Human Health Effects		
	Eyes	Not expected to cause irritation	
	Skin	May cause mild skin irritation if prolonged us	ed.
	Inhalation	Not expected to cause any side effect while i	nhalation
4.	First Aid Measures		
	Inhalation	If inhaled, remove to fresh air. Get medical a	ttention if symptoms occur.
	Skin contact	Immediately wash affected area with soap clothing and shoes. Get medical attentions if	a symptom occurs.
	Eye contacts	In case of contact immediately wash eyes wi	th plenty of water.
	Ingestion	Do not induce vomiting unless directed to give anything by mouth to an unconsciou quantities of this material have been swall Get medical attention if symptoms occur.	us person. If potentially dangerous
5.	Fire-fighting Measures		
	Flammability of product	Combustible liquid	
	Extinguishing Media Suitable Not suitable	Use dry chemical, carbon dioxide (CO_2), or for Do not use water	oam

6. Accidental Release Measures

Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Clean up method- small spillage	Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulation.

EASTTO NEAT CUTTING OIL 522 Revision No. 3 Date of issue: 10.11.2014 Date of revision: 17.08.2016



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web: www.easternpetroleum.in CIN NO: U24100MH1964PTC012931

	Clean up methods – large spillage	Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.	
7.	Handling and Storage		
	Handling	Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment, vapors or mists might be released and require a well ventilated workplace.	
	Storage	Store at ambient temperature or with lowest necessary heating as required for ease of handling.	
8.	Exposure Controls / Personal Protection		
	Control parameters	Use under well ventilated areas	
	Personal protection equipment		
	Respiratory protection Hand protection Eye protection	Avoid inhalation use suitable mask with filter if necessary. Wear oil-resistant protective gloves if there is a risk of skin contact. For eyes protection wear safety goggles. Use protective cloths and gloves.	

9. Physical and Chemical Properties

CHARCTERISTICS	EASTTO NEAT CUTTING OIL 522
Physical state	Liquid
Odour	Mild
Colour	Yellow
Sp. Gravity @ 30 °C, gm/ml	0.87
Kinematic viscosity @ 40 °C, cst	22
Solubility in water	Insoluble
pH	N.A
Flash point ⁰C	160

10. Stability and Reactivity

	Reactivity and stability Conditions to avoid Hazardous decomposition products Hazardous polymerization	Stable at normal conditions and decompose at higher temperature. Excessive heating and highly oxidizing agents Upon Combustion, CO_2 , CO and oxides of Sulphur and Nitrogen are generated. Under normal conditions of storage and use, polymerization will not occur.	
11.	Toxicological Information		
	Potential chronic health effects Carcinogenicity	No known significant effects or critical hazards.	
12.	Ecological Information		

12. Ecological Information

Environment effect:

Will not have chronic effect on aquatic environment

13. Disposal considerations

Waste disposal procedure:

Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.

14. Transport Information Not c

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

EASTTO NEAT CUTTING OIL 522 Revision No. 3



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web: www.easternpetroleum.in CIN NO: U24100MH1964PTC012931

15.	Regulatory Information	Not classified as hazardous
16.	Other Information	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.