

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

# **MATERIAL SAFETY DATA SHEET**

### 1. Product name and Company identification

Product Name	:	EASTTO HYDRAULIC OILS HLP ZF 32, 46, 68,100
Product Use	:	Industrial Hydraulic oil
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jawahar industrial Estate, Kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

# 2. Composition / Information of Ingredients

	Ingredient name	CAS Number	% by wt	
	Mineral base oil Proprietary additives	64742-65-0 Mixture	98 - 100 0 - 2	
3.	Hazards identification	Non dangerous substance		
	Physical state	Liquid		
	Human Health Effects			
	Eyes	Not expected to cause irritation		
	Skin	May cause mild skin irritation if prolonged use	ed.	
	Inhalation	Not expected to cause any side effect while in	nhalation	
4.	First Aid Measures			
	Inhalation	If inhaled, remove to fresh air. Get medical at	tention if symptoms occur.	
	Skin contact	Immediately wash affected area with soap and water. Remove contaminated clothing and shoes. Get medical attentions if a symptom occurs. In case of contact immediately wash eyes with plenty of water.		
	Eye contacts	Do not induce vomiting unless directed to o give anything by mouth to an unconsciou quantities of this material have been swallo Get medical attention if symptoms occur.	do so by medical personnel. Never is person. If potentially dangerous	
5.	Fire-fighting Measures			
	Flammability of product	Combustible liquid		
	Extinguishing Media Suitable Not suitable	Use dry chemical, carbon dioxide ( $CO_2$ ), or for Do not use water	bam	

### 6. Accidental Release Measures

Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Clean up method- small spillage	Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulation.

EASTTO HYDRAULIC OILS HLP ZF 32, 46, 68,100 Revision No. 3



#### Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

Clean up methods – large spillage Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.

#### 7. Handling and Storage

Handling

Storage

Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment, vapors or mists might be released and require a well ventilated workplace. Store at ambient temperature or with lowest necessary heating as required for ease of handling.

#### 8. Exposure Controls / Personal Protection

#### **Control parameters**

Use under well ventilated areas

Personal protection equipment

Respiratory protectionAvoid inhalation use suitable mask with filter if necessary.Hand protectionWear oil-resistant protective gloves if there is a risk of skin contact.Eye protectionFor eyes protection wear safety goggles.Skin and body protectionUse protective cloths and gloves.Hygienic measuresAct in accordance with good industrial Hygiene and safety practice.

# 9. Physical and Chemical Properties

CHARCTERISTICS	32	46	68	100
Physical state	Liquid	Liquid	Liquid	Liquid
Odour	Mild	Mild	Mild	Mild
Kinematic viscosity @ 40 °C, cst	32	46	68	100
Solubility in water	Insoluble	Insoluble	Insoluble	Insoluble
рН	N.A	N.A	N.A	N.A
Flash point <sup>o</sup> C	210	215	220	220

#### 10. Stability and Reactivity

	Reactivity and stability Conditions to avoid Hazardous decomposition products Hazardous polymerization	Stable at normal conditions and decomposes at higher temperature Excessive heating and highly oxidizing agents Upon Combustion, CO <sub>2</sub> , CO and oxides of Sulphur and Nitrogen are generated Under normal conditions of storage and use, polymerization will not occur
11.	Toxicological Information	
	Potential chronic health effects Carcinogenicity	No known significant effects or critical hazards.
12.	Ecological Information	
	Environment effect:	Will not have chronic effect on aquatic environment
13.	Disposal considerations	
	Waste disposal procedure:	Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.
14.	Transport Information	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)
15.	Regulatory Information	Not classified as hazardous.



#### Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

#### 16. Other Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.