

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO: U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:	EASTTO CONNING OIL 10	
INTRODUCTION:	EASTTO CONING OIL10 is emulsifiable oil and has been formulated from highly refined mineral oils and specially selected surface active agents to provide appropriate antistatic property. This oil is non-staining, with good emulsion stability and excellent antistatic properties.	
APPLICATION:	EASTTO CONING OIL 10 is used for all texturising / twisting / crimping operations for synthetic yarns. It is also used for softening and wetting of yarn during woolen, rayon cording and rayon conning operation.	







PERFORMANCE LEVEL:

EASTTO CONING OIL 10 is a proprietary grade.

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO CONNING OIL 10
Kinetic Viscosity at 40°C., cst	10
Colour, ASTM, Max.	1.0
Flash Point, COC, ºC	150
Emulsion Stability Test for 24 Hrs.	Passes

PACKING: 210 Litres Drums

Date of issue: 10.11.2014

Date of revision: 24.08.2016

PDS No. 10.01.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

