

PRODUCT DATA SHEET

PRODUCT: EASTTO SPINTEX OILS 5, 10, 12, 15, 22

INTRODUCTION: EASTTO SPINTEX OILS are low viscosity spindle oils are manufactured from highly refined base stocks fortified with anti oxidation, rust inhibitor, anti-wear and antifoam agents for better performance.

APPLICATION: EASTTO SPINTEX OILS are used for high speed spindles of Textile Mills and Machine Tools. These oils can also be used for Spindle bearing, Timing gears, Centrifugal separators, Positive displacement blowers and Hydraulic systems of high precision machine tools.



Spindle



Spindle Bearing



Timing gears

PERFORMANCE LEVEL: Proprietary Grades

TYPICAL PROPERTIES

EASTTO SPINTEX OILS					
TYPICAL PROPERTIES	5	10	12	15	22
Kinematic Viscosity at 40°C	5	10	12	15	22
Viscosity Index	--	90	90	90	90
Flash Point, COC, °C.	90	170	175	180	180
Pour Point, °C	-6	-6	-6	-6	-6

PACKING: 210 Litres Drums.

Date of issue: 31.12.2014

Date of revision: 11.08.2016

PDS No. 10.05.01 – 10.05.05

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

