

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in CIN NO: U24100MH1964PTC012931

# MATERIAL SAFETY DATA SHEET

1. Product name and Company identification

Product Name : EASTTO BAN 160

Product Use : Industrial Rust Preventive Oil

Supplier : Eastern Petroleum Pvt. Ltd

235-239, Jawahar Industrial Estate, Kamothe, Panvel,

Dist-Raigad, Maharashtra: 410209

**Telephone No.** : 91-22-2743 1694, 91-22-2743 3819.

Email : sales@easternpetroleum.in

2. Composition / Information of Ingredients

3. Hazards identification Non dangerous substance

Physical state Liquid

**Human Health Effects** 

Eyes Not expected to cause irritation

**Skin** May cause mild skin irritation if prolonged used

**Inhalation** Not expected to cause any side effect while inhalation

4. First Aid Measures

**Inhalation** If inhaled, remove to fresh air. Get medical attention if symptoms occur

Skin contact Immediately wash affected area with soap and water. Remove contaminated

clothing and shoes. Get medical attentions if a symptom occurs.

Eye contacts In case of contact immediately wash eyes with plenty of water.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never

give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.

Get medical attention if symptoms occur.

5. Fire-fighting Measures

Flammability of product Combustible liquid

**Extinguishing Media** 

Suitable Use dry chemical, carbon dioxide (CO<sub>2</sub>), or foam

Not suitable Do not use water.

6. Accidental Release Measures

Personal precautions Wear suitable protection clothing and equipment. Remove contaminated clothes

as soon as possible.

**Environmental precautions** Avoid dispersal of spilled material and runoff and contact with soil, waterways,

drains and sewers. Inform the relevant authorities if the product has caused

environmental pollution (sewers, waterways, soil or air).

**EASTTO BAN 160** 

Revision No. 3

Date of issue: 10.11.2014 Date of revision: 12.08.2016



## Eastern Petroleum Pvt. Ltd. an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO: U24100MH1964PTC012931

Clean up method- small spillage

Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly

marked container for disposal in accordance with local regulation.

Clean up methods - large spillage

Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for

small spills.

7. **Handling and Storage** 

Storage

Handling Handle in accordance with good industrial hygiene and safety practices. If

handled at elevated temperatures or with high speed mechanical equipment, vapors or mists might be released and require a well ventilated workplace.

Store at ambient temperature or with lowest necessary heating as required for

ease of handling.

8. **Exposure Controls / Personal Protection** 

> Use under well ventilated areas **Control parameters**

Personal protection equipment

Respiratory protection Avoid inhalation use suitable mask with filter if necessary.

Hand protection Wear oil-resistant protective gloves if there is a risk of skin contact.

For eyes protection wear safety goggles. Eye protection

Skin and body protection Use protective cloths and gloves.

Hygienic measures Act in accordance with good industrial Hygiene and safety practice.

#### 9. **Physical and Chemical Properties**

CHARCTERISTICS	EASTTO BAN 160
Physical state	Liquid
Odour	Mild
Colour	Brown
Sp. Gravity @ 30 °C (gm/ml)	0.87
Solubility in water	Insoluble
pH	N.A
Flash point °C	80

#### 10. **Stability and Reactivity**

Reactivity and stability

**Hazardous polymerization** 

Conditions to avoid

Hazardous decomposition products

Stable at normal conditions and decomposes at higher temperature

Excessive heating and highly oxidizing agents

Upon Combustion, CO<sub>2</sub>, CO and oxides of Sulphur and Nitrogen are generated

under normal conditions of storage and use polymerization will not occur

#### 11. **Toxicological Information**

Potential chronic health effects

Carcinogenicity No known significant effects or critical hazards.

#### 12. **Ecological Information**

**Environment effect:** 

Will not have chronic effect on aquatic environment

### 13. **Disposal considerations**

Waste disposal procedure:

Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations. Contact local environment and health authorities to get the permission for waste disposal.

14. **Transport Information**  Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

**EASTTO BAN 160** 

Date of issue: 10.11.2014 Revision No. 3 Date of revision: 12.08.2016



an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in CIN NO: U24100MH1964PTC012931

Date of issue: 10.11.2014

Date of revision: 12.08.2016

15. **Regulatory Information** Not classified as hazardous

16. **Other Information** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.