

PRODUCT DATA SHEET

PRODUCT: WHITE MINERAL OIL

GRADE: EASTTO LX-10, LX-15, LX-20, LX-30, LX-100

INTRODUCTION: It is a purified mixture of Liquid Saturated Hydrocarbons, obtained from Petroleum & are highly paraffinic in nature. It is Transparent, Colourless, and Tasteless & Odourless when cold. These highly refined hydro-treated oils, though less refined than their pharmaceutical counterparts have excellent thermal & chemical stability having high flash points & can be used for general industrial applications.

APPLICATION : It is used in the manufacture of Bulk Drugs, Cosmetics, Textile Auxiliaries, Plant Spray Oils, Agrochemicals, Aerosols, Insecticides Oils, Leather Process Oils, Dye Intermediates, Instrument Oils, Polishes, Paper Industry, Inks, Perfumery, Agarbatties, Speciality Lubricants, Polymers, Master-batches, Plastics – used as a Lubricant Plasticiser, Extender, Softener during processing of Plastics, Mould release agents etc.



TYPICAL PROPERTIES:

CHARACTERISTICS	LX-10	LX-15	LX-20	LX-30
APPEARANCE	WATER WHITE	WATER WHITE	WATER WHITE	WATER WHITE
SPECIFIC GRAVITY @ 15°C	0.8 – 0.81	0.82 – 0.84	0.825 – 0.85	0.83 – 0.85
K. VISCOSITY @ 40°C, cSt.	6 – 9	12 – 15	19 – 23	25 – 32
FLASH POINT Min °C	140	165	180	200

PACKING: 210 Litres M.S. Barrels / Tanker Loads

DATE OF ISSUE: 03.01.2015, PDS No.

These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of EASTERN PETROLEUM PVT. LTD.

