

Eastto Spintex Oils

INTRODUCTION : EASTTO SPINTEX OILS are recommended for the lubrication of high speed spindles of Textile Mills and Machine Tools. These low viscosity spindle oils are manufactured from highly refined base stocks having excellent oxidation and rust stability and further fortified with oxidation and rust inhibitor, antiwear and antifoam agents for better performance.

APPLICATION : EASTTO SPINTEX OILS are used for high speed spindles of Textile Mills and Machine Tools. These oils can also be used for spindle bearing, timing gears, centrifugal separators, positive displacement blowers and hydraulic systems of certain high precision machine tools.

TYPICAL PROPERTIES

EASTTO LOOM OILS N					
CHARACTERISTICS	5	10	12	15	22
KV at 40°C	4.5 - 5.5	9.0 - 11.0	11.0 - 13.0	14.0 - 16.0	20.0 - 24.0
VI, Min.	-	90	90	90	90
Flash Point, COC, °C. Min	70	100	140	140	170
Pour Point, °C. Max.	-6	-6	-6	-6	-6

PACKING: 210 Litres M.S. Barrels / Tanker Loads



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Spintex Oils



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

