

Eastto Neat Cutting Oil 442

INTRODUCTION: EASTTO NEAT CUTTING OIL 442 contains sulphurised fat and chlorinated additives to impart extreme pressure property to cutting operations of low speeds at low or moderate temperature.

APPLICATION: EASTTO NEAT CUTTING OIL 442 is recommended for multipurpose machining operations of ferrous and non ferrous metals without discolouration, e.g. Gear hobbing and shaving, Spline hob cutting, Drilling, Tapping, Broaching, dip hole drilling, Milling, Reaming, Gear chamfering, Notching and Punching.

PERFORMANCE LEVEL : EASTTO NEATCUTTING OIL 442 is a proprietary product.

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO NEATCUTTING OIL 442
Kinematic Viscosity at 40°C, cSt	46
Flash Point, COC,°C	180
Copper Strip Corrosion for 3 Hrs. at 100°C	1
Sap Value, mg KOH/gm	4

PACKING: 210 Litres Drums



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Neat Cutting Oil 442