

Eastto Neat Cutting Oil 522

INTRODUCTION: EASTTO NEAT CUTTING OIL 522 contains fatty oil and chlorinated additives to improve machine ability with reduction of wear on tool life and gives better surface finish without discolouration of the components.

APPLICATION: EASTTO NEAT CUTTING OIL 522 is recommended for multipurpose machining operations of ferrous and non-ferrous metals including different Grinding, Drilling, Honing, Milling, Gear tooth grinding, Gun reaming, Fine boring, Deep hole drilling, punching, Surface broaching and Gear chamfering operations.

PERFORMANCE LEVEL : EASTTO NEAT CUTTING OIL 522 meets the requirement of IS 3065-1985, TYPE I, Grade 2 (RE-AFFIRMD 2002).

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO NEATCUTTING OIL 522
Kinematic Viscosity at 40°C, cSt	22
Flash Point, COC,°C	160
Copper Strip Corrosion for 3 Hrs. at 100°C	1
Sap Value, mg KOH/gm	7

PACKING: 210 Litres Drums



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Neat Cutting Oil 522