

Eastto Neat Cutting Oil 932

INTRODUCTION: EASTTO NEAT CUTTING OIL 932 contains active and non-active sulphur, fatty oil and chlorinated additives to give better surface finish and longer cutting tool life over a wide range of operating temperatures by providing an excellent lubricating film.

APPLICATION: EASTTO NEAT CUTTING OIL 932 is recommended for machining operations of gear shaping, boring, punching, surface broaching, gear tooth grinding and threading of alloy and stainless steels.

PERFORMANCE LEVEL : EASTTO NEAT CUTTING OIL 932 meets the requirement of IS 3065-1985, TYPE III, Grade 2 (RE-AFFIRMD 1995)

CHARACTERISTICS	EASTTO NEATCUTTING OIL 932
Kinematic Viscosity at 40°C, cSt	34 - 40
Flash Point, COC, °C	160
Copper Strip Corrosion for 3 Hrs. at 100°C	4
Sap Value, mg KOH/gm	10

PACKING: 210 Litres Drums



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Neat Cutting Oil 932