

Eastto Quench HS 70

Eastto Quench HS 70

INTRODUCTION: EASTTO QUENCH HS 70 is high speed quenching oil blended from highly refined paraffinic base oils and special additives to optimize heat resistance to the oxidation and to adhere to the surface of the working piece by providing bright finish due to reduced sludge forming tendencies with minimum distortion. EASTTO QUENCH HS 70 exhibits excellent thermal stability retains its original viscosity in normal service and has high flash point to minimize fire hazards.

APPLICATION: EASTTO QUENCH HS 70 is recommended when deeper and more uniform hardening is required in ferrous metals such as Carbon steel, Gray iron and High-alloy steel. It is used in quenching of Crank shafts, Nut bolts, Bright bars, Tools, Automotive components and Industrial components

PERFORMANCE LEVEL: PROPRIETARY PRODUCT

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO QUENCH HS 70
Kinematic Viscosity at 100°C., cSt,	15
Flash Point, COC, °C.	170
Pour Point, °C. Max.	-9

PACKING: 210 Litres Drums



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Eastto Quench HS 70