

PRODUCT DATA SHEET

PRODUCT: EASTTO PET 30 - CALCIUM PETROLEUM SULPHONATE

INTRODUCTION: EASTTO PET 30 is a Calcium Petroleum Sulphonate. The increased oil solubility of the organic portion of this Sulphonate enables the product to provide rust protection and acts as dispersant for graphite and molybdenum disulfide.

APPLICATION: It is used in Manufacture of Rust Preventive Compounds in gasoline and Diesel Engine oils to control piston deposits and Hydraulic oils as detergent additive. It is used in formulation of Metal Working fluids. It is also used for Protective coatings, Corrosion inhibitors, Lubricants and Lube oil additive.



It is used in formulation of Metal working fluids, Protective coatings, Greases etc.

PERFORMANCE LEVEL: Proprietary product

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO PET 30
Appearance	Dark Brown Viscous Liquid
Active Matter (as Calcium Sulphonate, Wt. %)	42
Mineral Oil Content, Wt. %	60
Kinematic Viscosity @ 100° C, cst	222
Calcium Content, Wt. %	2.74
TBN, mg KOH/gm.	28
Flash Point(COC) ° C Min.	140

PACKING: 200 Kgs of M.S. Barrels.

Date of issue : 24.12.2014

Date of Revision: 09.08.2016

PDS No. 20.06.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

