

PRODUCT DATA SHEET

PRODUCT: EASTTO GEM 15W-40 CI-4

INTRODUCTION: EASTTO GEM 15W-40 CI-4 is premium quality diesel engine oil. It is formulated from highly refined base stocks and superior quality additives for high viscosity index and excellent detergent-dispersant inhibition to keep engine clean, prevent oil degradation / thickening and corrosive wear. It is also provide long draining periods, extended TBN retention and reduced oil consumption with better fuel economy.

APPLICATION: It is recommended for diesel passenger cars and commercial heavy duty diesel engines on-highway and off-highway equipment, like mining, earthmoving, construction industry and DG sets, and also for gasoline engines.



Heavy duty diesel engines on-highway and off-highway like Mining, Earthmoving construction industry and DG sets.

PERFORMANCE LEVEL: Meets the performance level of API CI-4

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO GEM 15W-40 CI-4
Kinematic Viscosity at 100°C, cst	14.0
Flash Point, COC, °C,	210
TBN, mg KOH / gm	10.5
Pour Point, °C	(-) 21

PACKING: 210 Litres Drums

Date of issue: 06.09.2014

Date of revision: 24.08.2016

PDS No. 01.07.01 – 01.07.02

These Characteristics are typical of current production while future production will confirm to EASTERN PETROLEUM PVT. LTD. Specification variation in these characteristics may occur.

