

Eastto GROUP II BASE OILS

EASTTOLX - 30 & LX 100

INTRODUCTION: American Petroleum Institute (API) classifies quality levels of Base Oils used by the Petroleum Industry into five categories from Group I to V. Group II Base Oils are classified as those which have saturates above 90%, have sulphur less than 0.03% (by weight) and VI between 80 to 120.

Eastern Petroleum offers Group II Base Oils exceed the minimum API stipulations and have VI of 118 (Typical). The higher percentage of saturates in these grades makes them excellent colour and oxidation stability.

Having undergone the hydro-finishing process, which helps to convert the aromatics to naphthenic, EASTTO PET LX -30 & EASTTO PET LX-100 Base Oils also have good thermal stability.

APPLICATION: These base oils are preferred in blending of Engine oils, Industrial and Specialty Lubricants, Neat Cutting oils, Transformer oil, Heat Transformer oil, Moulding oils even Process Oils where excellent oxidation and thermal stability are needed.

Their water-white colour makes them readily acceptable by many industries, e.g. Textile, Colour, rubber-manufacturing, white molded articles, etc. where stains are not acceptable.

PERFORMANCE LEVEL:

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO LX 30	EASTTO LX 100
Appearance	Clear & Bright	Clear & Bright
Flash Point, COC, °C	226	246
Density @ 15°C	0.840	0.850
KV at 40°C	32	95

PACKING: 210 Litres M.S. Barrels/Tanker Load.



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
*Group II Base Oils ,
LX-30, LX-100*