

PRODUCT DATA SHEET

PRODUCT: EASTTO GROUP II BASE OILS

GRADE: EASTTO LX – 30, LX 100

INTRODUCTION: EASTTO LX-30, LX- 100 is hydro cracked group II base oils. They have undergone hydro processing which increases the level of saturates and purges out impurities. They have good performance in lubricating properties such as Volatility, Oxidative stability, High viscosity index and Flash or fire points. They have also good performance in areas such as pour point, Cold crank viscosity and extreme pressure wear properties.

APPLICATION: These base oils are preferred in blending of Engine oils, Industrial and Speciality Lubricants, Neat Cutting oils, Greases, Transformer oil, Heat Transformer oil and Moulding oils even Process Oils where excellent oxidation and thermal stability are needed.



Used in Automotive oil, Heat transfer system, Rubber Manufacturing etc.

TYPICAL PROPERTIES:

| CHARACTERISTICS | EASTTO LX- 30 | EASTTO LX- 100 |
|-----------------------------|----------------|----------------|
| Appearance | Clear & Bright | Clear & Bright |
| Flash Point °C | 210 | 240 |
| Density @ 15°C | 0.840 | 0.850 |
| Kinematic viscosity at 40°C | 32 | 95 |

PACKING: 210 Litres M.S. Drums / Tanker Load

Date of issue: 09.09.2014

Date of Revision: 16.08.2016

PDS No. 01.31.02 / 01.31.04

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

