

Eastto EASTOPET 60 - Sodium Petroleum Sulphonate

INTRODUCTION: It is obtained from sulfonation of base oil, neutralized by Sodium Hydroxide. The Product mainly works as a Surface Active Agent, Emulsification & Dispersion of Liquids, Wetting and Dispersion of Liquid – Solid System, Inhibition of Rust & Corrosion, Dispersion and Wetting of Solids.

APPLICATION: It is widely used in the manufacture of Soluble Cutting Oils, Emulsifiers of Soluble Cutting Oils, Rust Preventives, Leather Chemicals, Fat Liquor, Metal Treatment Chemicals, Metal working fluid, Wire drawing oils, Corrosion inhibitors, Protective coatings, Degreasing agent, Fuel additive, Lube oil additive, Textile Auxiliaries, ore Flotation Chemicals, Inks etc. This product is miscible with Oil and Solvent.

PERFORMANCE LEVEL :

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO PET 30
Appearance	Dark Brown Viscous Liquid
Active Matter (as Calcium Sulphonate, Wt. %)	60 - 62
Mineral Oil Content, Wt. %	35 - 30
Inorganic Salt (as Sodium Sulphate, Wt. %)	1.0
Water, Wt. %	3.0
Alkalinity (as NaOH, Wt. %)	0.15 Max.
Acidity, Wt. %	Nil.
Average Molecular Weight	450 - 480

PACKING: 210 Litres Drums



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



EASTOPET 60 Sodium Petroleum Sulphonate



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

