

Eastto Refrigeration Oils

GRADES: VG 12, 22, 32, 46, 68 & 100

INTRODUCTION:

Eastto Refrigeration Oils - 12, 22, 32, 46, 68 & 100 - possess very high fluidity at very low temperatures (low pour point) with low flock point, resist deposit formation; have good chemical stability with minimum tendency to foam. They also have good oxidation and thermal stability.

APPLICATION:

EASTTO REFRIGERATION OILS - 12, 22, 32, 46, 68 & 100 - are recommended for lubrication of a wide range of refrigeration compressors of open, hermetically sealed and semi-sealed reciprocating and rotary type using conventional type refrigerants (except SO₂) at moderate thermal load.

Performance Level: Meet IS-4578 – 1997 requirements.

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO REFRIGERATION OILS					
	12	22	32	46	68	100
kinematic Viscosity at 40°C, cSt	12 to 14	20 to 24	30 to 34	44 to 48	66 to 70	95 to 105
Flash Point, COC, °C, Min.	140	140	150	160	170	200
Pour Point, °C. Max.	Minus 39	Minus 39	Minus 30	Minus 27	Minus 24	Minus 24
Viscosity Index, Min.	55	55	55	55	55	60

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Refrigeration Oils

Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

