

Eastto Steel EP

GRADE: VG 100, 150, 220, 320, 460

INTRODUCTION :

EASTTO STEEL EP 100, 150, 220, 320 & 460 are premium quality heavy duty bearing and circulating oils with excellent demulsibility characteristics, superior oxidation and thermal stability.

APPLICATION : EASTTO STEEL EP 100, 150, 220, 320 & 460 are recommended for use in rod mills and in the applications where severe load conditions are encountered.

PERFORMANCE LEVEL : Proprietary

TYPICAL PROPERTIES:

EASTTO STEEL EP					
CHARACTERISTICS	100	150	220	320	460
Kinematic Viscosity @ 40°C, cSt.	95 to 105	145 to 155	210 to 230	310 to 330	440 to 480
Viscosity Index	95	95	90	90	90
Flash Point, °C (COC), Min.	210	210	220	220	260
Pour Point, °C, Max.	-6	-6	-6	-6	-6

PACKING : 210 Litres Drum



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Steel EP



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

