

PRODUCT DATA SHEET

PRODUCT: EASTTO METAL DRAWING 15 AL

GRADE: VG 320

INTRODUCTION: EASTTO METAL DRAWING 15 AL is manufactured from highly refined base stocks and specially selected additives to impart high wetting and excellent EP properties with good metal deactivation, anti-rust and anti-wear properties. This product has excellent load carrying capacity which is encountered in metal drawing and is capable of stopping any wire leakage even with high speed drawing.

APPLICATION: EASTTO METAL DRAWING 15 AL is suitable for wire drawing operations of Aluminum and its alloys even at high speeds.



Drawing of aluminum and other aluminum alloys even with high speed.

PERFORMANCE LEVEL: EASTTO METAL DRAWING 15 AL is a proprietary product.

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO METAL DRAWING 15 AL
Kinematic Viscosity at 40°C, cst	320
Flash Point °C(COC) Min.	250
Copper Strip Corrosion for 3 Hrs at 100°C.	1
Saponification No., mg KOH / gm	20

PACKING: 210 Litres Drums

Date of Issue : 01.07.2009

Date of revision: 04.08.2016

PDS No. 05.70.21

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

