

**PRODUCT DATA SHEET**

**PRODUCT:** EASTTO BAN 4050 BB

**GRADE:** BITUMEN BASED RUST PREVENTIVE

**INTRODUCTION:** EASTTO BAN 4050 BB is a black liquid of medium viscosity comprised of soft bitumen compound and suitable solvent. When the solvent portion from EASTTO BAN 4050 BB is evaporated, the product leaves on the coated part as a tacky film that does not dry very hard as in the case of paints.

**APPLICATION:** EASTTO BAN 4050 BB is applied by brush or swab. EASTTO BAN 4050 BB is suitable for protecting metals exposed to high temperatures and under mild acidic and alkaline conditions. EASTTO BAN 4050 BB is recommended for structural frames, metallic pipes, gates, bridges, tanks farm equipments etc.



BAN 4050 BB is recommended for structural frames, metallic pipes, gates, bridges, etc.

**PERFORMANCE LEVEL:** EASTTO BAN 4050 BB is a proprietary product.

**TYPICAL PROPERTIES**

CHARACTERISTICS	X	EASTTO BAN 4050 BB
Appearance		Dark free following liquid
Kinematic Viscosity at 40°C		55
Flash Point, PMCC, °C, Min.		140
Copper Strip Corrosion Test at 100°C for 3 Hrs.		1

**PACKING:** 210 Litres Drums

**Date of issue:** 10.11.2014

**PDS No.** 50748

These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of EASTERN PETROLEUM PVT. LTD.

