

PRODUCT DATA SHEET

PRODUCT: EASTTO OPEN GEAR COMPOUNDS

GRADES: 100, 225, 475, 950

INTRODUCTION: EASTTO OPEN GEAR COMPOUNDS - 100, 225, 475, 950, are bituminous Lubricant containing EP and special tackiness additives to provide stringiness and excellent film strength to encounter high pressure developed from heavily loaded open gear. These compounds are having good load carrying capacity and rust preventing properties.

APPLICATION: EASTTO OPEN GEAR COMPOUNDS -100, 225, 475, 950 are recommended For lubrication of Open gears, Wire ropes and Chain drives and also for lubrication of Kiln Tyres operating at high temperatures in Cement Mills and Chemical Plants. It is also used in Mining applications include all types of open Gears, Rails and rollers, Racks and pinions, Dipper sticks and other slides on Shovels and Draglines.



Opengear compounds for high temperatures in Cement Mills and Chemical Plants.

PERFORMANCE: Proprietary Product

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO OPEN GEAR COMPOUNDS			
	100	225	475	950
Appearance	Viscous liquid	Viscous liquid	Viscous liquid	Viscous liquid
Colour	Black	Black	Black	Black
Kinematic Viscosity at 100°C, cst	100	230	460	950
Flash Point(COC), °C	260	260	280	280

PACKING: 210 Litres Drums
Date of Issue: 14.09.2014
Date of Revision: 08.08.2016
PDS No. 03.46.01 – 03.46.04

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

