

PRODUCT DATA SHEET

PRODUCT: EASTTO MAX - 80 (PARAFFINIC RICH LOW AROMATIC SOLVENT).

INTRODUCTION: This is chemically processed specially formulated solvent, free from Aromatics and unsaturated hydrocarbons, almost odourless clear and colourless liquid.

APPLICATION: This highly paraffinic low viscosity product is obtained from selective treatment, refining & distillation of refined speciality base stocks & is available in a wide range of boiling ranges. This product is widely used in manufacture of Polish, metal degreasing products, specialty lubricants, agrochemicals, paint industries, printing ink industries, rust preventives, lube oil additives, pesticides, insecticide, specialty chemicals, fly sprays, fuel additive, mosquito repellents and as a general purpose solvent for Industrial application.



Agrochemicals Paint industries.

TYPICAL PROPERTIES:

Sr. No.	PROPERTIES	EASTTO MAX – 80
1	Appearance	Bright & Clear Colourless Liquid, free from foreign particles
2	Colour(Saybolt)	+30
3	Odour	Odourless, Non - Offensive
4	Specific Gravity @ 25°C	0.78 + 0.01
5	Flash point(PMCC) °C	85 + 2 °C
6	Kinematic Viscosity at 40 °C, cst	1.65 + 0.05
7	% Aromatics	Less than 1%
8	% Sulphur , ppm	Less than 50 ppm
9	BOILING RANGE - IBP	210 + 5 °C
	FBP	233 + 5 °C
10	Recovery, %	98 % min

PACKING: 210 Litres M.S. Drums/ TANKER LOAD.

Date of issue: 24.12.2014, **PDS No.** 17.12.2012

These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of EASTERN PETROLEUM PVT. LTD.

