

PRODUCT DATA SHEET

PRODUCT: EASTTO 'LIQUID PARAFFIN –IP'.

INTRODUCTION: it is a purified mixture of liquid hydrocarbons and having a dynamic viscosity of 110 to 230 mPas. It is free of sulphur and is used as a carrier (vehicle) in pharmaceutical industry. Is is a transparent, colourless oil, free from fluorescence by day-light, almost odourless & tasteless when cold. It is highly refined oil having excellent chemical stability and high flash point.

APPLICATION: This oil is used in the manufacture of Anti-static Coning Oils, knitting Oils & Other Textile Auxiliaries, Plant Spray Oils, Agrochemicals, Aerosols, Dye Intermediates, Paper Industry; Perfumery, Food Grade Speciality Lubricants, Food Grade Plastics- used as a Lubricant Plasticizer, Attars, Flavours & Fragrances, Perfumery Chemicals, Speciality Chemicals, Incenses, Personal Care Products, Leather Chemicals, Fat Liquors, Petrochemical Solvents, etc.This may also be used in the manufacture of Pharmaceuticals and Cosmetic Products like Creams, Lotions, Perfumery Industry, Bulk Drugs & Food Industry etc.



Cosmetic Products & Food Industry, etc.

TYPICAL PROPERTIES:

CHARACTERISTICS	LIQUID PARAFFIN- IP
Acidity / Alkalinity	Passes as per I.P.
Dynamic Viscosity @ 20°C	Between 110 to 230 mPas
Light Absorption @ 240-290 nm	Less than 0.1
Readily Carbonisable Substances Test	Passes as per I.P.
Weight /ML @25°C	0.85 to 0.880
Flash Point (COC)	200
Solubility	Passes
Sulphur	Passes
Solid Paraffins	Passes

PACKING : 210 Litres M.S. Barrels. / Tanker Loads.

These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of **EASTERN PETROLEUM PVT. LTD.**

