

**PRODUCT DATA SHEET**

**PRODUCT:** EASTTO PET 1400 - MAGNESIUM PETROLEUM SULPHONATE

**INTRODUCTION:** It is manufactured from Sulphonic acid, produced from synthetic base stock, Neutralised with Magnesium Hydroxide.

**APPLICATION:** It is used in the manufacture of Engine Oils and Industrial Lubricants. It also works as a detergent type Additive. It is also used in Fuel Additives, which helps in better combustion of Fuel in Engine and thus Soot Formation is reduced in the system.



Engine Oils.

**TYPICAL PROPERTIES:**

CHARACTERISTICS	EASTTO PET -1400
Appearance	Dark Brown Viscous Liquid
Specific Gravity @ 15.6 / 15.6°C	1 to 12
Magnesium, Wt. %	8- 9.60
TBN, mgKOH/gm.	380- 400
K. Viscosity @ 100° C, cSt.	50
Flash Point, (PMCC), Min.	140

**PACKING:** 200 Kgs. M.S. Barrels.

**DATE OF ISSUE:** 09.09.2014

**PDS No.** 20.15.02

**EASTERN PETROLEUM PVT. LTD.** These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of **EASTERN PETROLEUM PVT. LTD.**

