

Eastto Process Oils

EASTTO

GRADE: VG 22, 32, 46, 68, 100, 150, 220, 320 & 460

INTRODUCTION:

Eastto PROCESS OILS are highly refined solvent neutral base oils and have good inherent oxidation and thermal stability, non-corrosive, excellent ability to separate from water and high viscosity index with light colour

APPLICATION:

EASTTO PROCESS OILS are generally suitable for manufacturing of different lubricants, for non-critical all loss lubrication systems and other oiling applications. These oils are also recommended for flushing of inaccessible internal surfaces of various automotive and industrial equipments.

PERFORMANCE LEVEL: IS:493 (Part 1):1981 [Reaffirmed November, 1998]

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO PROCESS OILS								
	22	32	46	68	100	150	220	320	460
kinematic Viscosity at 40°C, cSt	20 to 24	30 - 34	43 - 49	64 - 72	95 - 105	145 - 155	210 - 230	300 - 340	440 - 480
Viscosity Index	90	90	90	90	90	90	90	90	90
Flash Point, COC, °C, Min.	160	160	160	160	170	190	200	220	240
Pour Point, °C. Max.	-6	-6	-6	-6	-6	-6	-6	-3	-3

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Process Oils



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

